



NaBr TABLE

an *imdex* limited company

Sp Gr	Density	Weight %	NaBr 94/97%	NaBr 94/97%	Water	Crystal Pt
	lb/gal 21°C	%	lb/bbl	kg/m ³	m ³ /m ³	°C
1.080	8.99	9.7	36.4	104.0	0.9735	-4
1.090	9.07	10.8	41.2	117.5	0.9703	-4
1.100	9.15	12.0	46.0	131.1	0.9670	-5
1.110	9.24	13.1	50.7	144.7	0.9637	-6
1.120	9.32	14.2	55.5	158.4	0.9603	-7
1.130	9.40	15.3	60.3	172.0	0.9569	-7
1.140	9.48	16.3	65.1	185.6	0.9534	-8
1.150	9.57	17.4	69.8	199.3	0.9498	-9
1.160	9.65	18.4	74.6	213.0	0.9463	-9
1.170	9.73	19.4	79.4	226.6	0.9426	-10
1.180	9.82	20.4	84.2	240.3	0.9390	-11
1.190	9.90	21.4	89.0	254.0	0.9353	-12
1.200	9.98	22.4	93.8	267.7	0.9315	-13
1.210	10.07	23.3	98.7	281.5	0.9277	-13
1.220	10.15	24.3	103.5	295.2	0.9239	-14
1.230	10.23	25.2	108.3	309.0	0.9201	-15
1.240	10.32	26.1	113.1	322.7	0.9162	-16
1.250	10.40	27.0	118.0	336.5	0.9123	-17
1.260	10.48	27.9	122.8	350.3	0.9084	-18
1.270	10.57	28.8	127.6	364.1	0.9044	-18
1.280	10.65	29.6	132.5	377.9	0.9005	-19
1.290	10.73	30.5	137.3	391.8	0.8965	-20
1.300	10.82	31.3	142.2	405.6	0.8925	-21

Sp Gr	Density	Weight %	NaBr 94/97%	NaBr 94/97%	Water	Crystal Pt
	lb/gal 21°C	%	lb/bbl	kg/m ³	m ³ /m ³	°C
1.310	10.90	32.1	147.0	419.5	0.8885	-22
1.320	10.98	32.9	151.9	433.3	0.8844	-23
1.330	11.07	33.7	156.7	447.2	0.8804	-23
1.340	11.15	34.5	161.6	461.1	0.8764	-24
1.350	11.23	35.3	166.5	475.0	0.8723	-25
1.360	11.31	36.1	171.4	488.9	0.8683	-26
1.370	11.40	36.8	176.3	502.8	0.8642	-27
1.380	11.48	37.6	181.1	516.8	0.8602	-27
1.390	11.56	38.3	186.0	530.7	0.8562	-28
1.400	11.65	39.0	190.9	544.7	0.8522	-29
1.410	11.73	39.7	195.8	558.7	0.8481	-28
1.420	11.81	40.5	200.7	572.7	0.8441	-26
1.430	11.90	41.2	205.6	586.7	0.8401	-24
1.440	11.98	41.8	210.5	600.7	0.8362	-22
1.450	12.06	42.5	215.5	614.7	0.8322	-18
1.460	12.15	43.2	220.4	628.8	0.8283	-14
1.470	12.23	43.9	225.3	642.8	0.8244	-11
1.480	12.31	44.5	230.2	656.9	0.8205	-7
1.490	12.40	45.2	235.2	671.0	0.8166	-2
1.500	12.48	45.8	240.1	685.1	0.8128	2
1.510	12.56	46.4	245.1	699.2	0.8090	6
1.520	12.65	47.1	250.0	713.3	0.8053	9
1.530	12.73	47.7	255.0	727.4	0.8015	13

Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.



Quality
ISO 9001
SAI GLOBAL

With more than 20 years experience, AMC has enjoyed a successful history of supplying specialist drilling products to the mineral, oil & gas, water well, horizontal directional drilling, civil and tunnelling industries world wide.

The success of AMC is due to its quality products, and the dedication of its skilled team who offer on site support where and when customers need it.

amc@imdexlimited.com

www.amcmud.com

AMC Africa
T +27 (0) 11 908 5595

AMC Asia Pacific
T +61 (0) 8 9445 4000

AMC Europe
T +44 (0) 1273 483 700

AMC North America
T +1 (403) 259 5112

AMC South America
T +56 (2) 589 9300