

AMC GROUT 20™

CEMENT & GROUTING ADDITIVES



Description

AMC GROUT 20™ is an abandonment and grouting material designed to be mixed with fresh water to form a semi rigid plug.

Application

AMC GROUT 20™ is designed to be applied as a 20% solids mix. The mixture is pumpable using most common pumping equipment.

Typical Physical Properties

Appearance: Dark red to brown powder

Solubility in water: Insoluble

Recommended Treatment

In order to mix a 20% solids slurry 250kg of AMC GROUT 20™ should be mixed into 1000L of fresh water. Alternatively, a 50lb bag of AMC GROUT 20™ should be mixed per 24 gal of fresh water.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000

E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 483 700

SOUTH AMERICA

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru/Ecuador

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095