AMC HARD SET™

CEMENT AND GROUTING ADDITIVES



Description

AMC HARD $\mathsf{SET}^{\mathsf{m}}$ is a specially formulated fast setting, high strength cement.

Application

AMC HARD SET™ has been specifically formulated for use in dust suppression and cementing of collar pipes in RC, diamond and water well drilling applications.

Due to its accelerated setting time, the use of mechanical pumping equipment is not recommended.

Recommended Treatment

Add 5 L of water to 8 kg of AMC HARD SET^m. Initial set in 3 – 4 minutes, final set in 5 – 6 minutes.

Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.

Advantages

- Due to rapid setting time, rig idle time is considerably reduced
- Can be mixed quickly and poured into surface fissures to combat dust.

ASIA PACIFIC

Perth, Australia (Head Office)

- T +61 8 9445 4000
- E amc@imdexlimited.com

Indonesia

T +62 (0) 21 759 11244

AFRICA

South Africa

T +27 (11) 908 5595

EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095