

# AMC WELLCLEAN™

## FLOCCULANTS & DISPERSANTS



### Description

AMC WELLCLEAN™ is used in the development and clean up of water wells where bentonite based mud has been used. AMC WELLCLEAN™ breaks down the viscosity of a bentonite mud and will disperse any wall cake that has formed on the walls of the drill hole, promoting rapid and effective clean up.

### Application

During development, the mud should be displaced from the drill hole with fresh water before adding AMC WELLCLEAN™.

After the well screens have been run and set, jetting and surging with an AMC WELLCLEAN™ / water mix will promote rapid, deep penetration of the aquifer and assist the well clean up.

### Typical Physical Properties

Appearance:	White powder
Specific gravity:	2.2 – 2.35
Solubility:	Soluble in water
pH (10% solution):	3 – 5

### Recommended Treatment

Add 3 – 5 kg /m<sup>3</sup> (1 – 1.75 lb / bbl) to clean water for jetting / surging through the screens or gravel pack.

*Please Note: Several factors will dictate the most appropriate concentration rate. Please contact your nearest AMC representative for optimum results.*

### Advantages

- Fast acting
- Effective at low concentrations
- Facilitates removal of calcium and magnesium ions from hard water
- Reduces pH in cement contaminated fluids.

#### ASIA PACIFIC

Perth, Australia (Head Office)

T +61 8 9445 4000

E [amc@imindexlimited.com](mailto:amc@imindexlimited.com)

Indonesia

T +62 (0) 21 759 11244

#### AFRICA

South Africa

T +27 (11) 908 5595

#### EUROPE

Germany

T +49 4402 6950-0

United Kingdom

T +44 (0) 1273 405 975

#### SOUTH AMERICA

Argentina

T +54 (9) 261 426 1116

Brazil

T +55 (47) 3404 5920

Chile

T +56 (2) 2589 9300

Peru

T + 51 (1) 322 8850

#### NORTH AMERICA

USA / Canada

T +801-364-0233

Mexico

T +52 (871) 169 2095